




BIG FOOT™ ANTI-SLIP COATINGS



BENEFITS

LOCTITE® BIG FOOT™ ANTI-SLIP COATINGS

- Outlast and outperform sand and paint
- The strongest, most aggressive anti-slip products available
- Resist harsh chemicals such as gasoline, jet fuel, and hydraulic fluid
- Prevent costly slips and falls where you have pedestrian traffic
- Tough enough to handle heavy fork lift and vehicular traffic
- Increase safety of walkways, ramps, and entrances
- Contaminants are trapped in the “valleys” and traction is maintained at the “peaks”

1 STEP ONE: SURFACE PREP

The surface must be:
1. Clean. 2. Dry. 3. Rough. Remove loose or flaking material. (Use mechanical brush or bead blast.) If wood, remove loose material.

If surface is oily, remove oils and surface contaminants with Loctite® Natural Blue® Cleaner.

Use hot, high pressure wash to remove cleaners and contaminants. Allow surface to completely dry.

2 STEP TWO: OUTLINE APPLICATION AREA

Outline area where Big Foot™ is to be applied using duct tape. (This makes clean edges).

3 STEP THREE: APPLY PRIMER

Mix and apply primer. Allow 3 hours to dry. The primer will turn from milky white to clear. Make sure that the primer is not tacky to the touch before continuing.

4 STEP FOUR: MIX PRODUCT

If using a two component product, mix two parts thoroughly. If using one part product, mix for approx. 3 minutes to insure proper aggregate mix.


5 STEP FIVE: APPLY PRODUCT

Pour thoroughly mixed product onto surface.

Roll-on product using Phenolic rollers.

Use light pressure to completely cover surface.

Remove tape outline before product has completely dried.



APPLICATIONS:

Use on Sidewalks, Equipment
Ramps, Floors, Entryways

Big Foot™ Low Profile Pedestrian Grade

A two-component, water-borne epoxy for recreation and bare foot traffic areas.

Big Foot™ Heavy Duty Pedestrian Grade

For areas with heavy pedestrian or light rolling traffic. Ideal for ramps, walkways, locker rooms, stairs, and assembly areas.

Big Foot™ Acrylic Pedestrian Grade

A single-component, elastomeric, anti-slip floor and deck coating for optimum adhesion to asphalt and flexible applications.

Big Foot™ Vehicular Grade

Withstands even the heaviest rolling equipment traffic. Resists liquids as harsh as jet fuels and hydraulic fluids. Superior adhesion forms a solid bond to metal, concrete, and wood.

Big Foot™ Zero V.O.C.

This 100% reactive, solvent-free epoxy has the most aggressive profile in the Big Foot line. Use in odor-sensitive areas such as wineries, food processing plants, hospitals, or for confined spaces.

Big Foot™ Glow Coat

A unique, glow-in-the-dark formula gives off a luminescent glow in total darkness for up to four hours after only a few seconds of exposure to artificial light. For indoor use only.

Big Foot™ Metal Primer

Two-component, epoxy-polyamide primer increases adhesion between Big Foot anti-slip coatings and metal surfaces.

Big Foot™ Acrylic Primer

A single-component, clear, zero V.O.C., water-based primer designed for use with Big Foot™ Acrylic Pedestrian Grade coating.

Big Foot™ Primer/Sealer

Specially formulated to increase adhesion and coverage of all Big Foot anti-slip coatings. For use on concrete, wood, tile, and other porous substrates. Water-based.

PROPERTIES CHART

PRODUCT	Item Number	Container	Coverage	Color	Mixed viscosity, cp	Maximum temperature, °F	Working time, minutes	Functional cure, hours	Mix ratio by weight, r:h
Big Foot™ Low Profile Pedestrian Grade	95631	1 gal. kit	90 ft ²	Black Grey	—	140	60	12	N/A
	95641	1 gal. kit							
Big Foot™ Heavy Duty Pedestrian Grade	96211	1 gal. can	50 ft ²	Black Grey	12,500	140	N/A	12	N/A
	96261	1 gal. can							
	96215	5 gal. pail							
	96265	5 gal. pail							
Big Foot™ Acrylic Pedestrian Grade	95591	1 gal. pail	70 ft ²	Grey	—	140	N/A	12	N/A
Big Foot™ Vehicular Grade	96221	1 gal. kit	40 ft ²	Black Grey	11,000	140	120	12	18:1
	96251	1 gal. kit							
	96225	5 gal. kit							
	96255	5 gal. kit							
Big Foot™ Zero V.O.C.	96231	1 gal. kit	35 ft ²	Black Grey	10,000	140	60	24	8.5:1
	39915	1 gal. kit							
	96235	5 gal. kit							
	96245	5 gal. kit							
Big Foot™ Glow Coat	96271	1 gal. can	70 ft ²	Luminescent	10,000	140	N/A	4	N/A
Big Foot™ Metal Primer	96132	1 gal. kit	250 ft ²	Clear	3,000	140	240	12	5.25:1
Big Foot™ Acrylic Primer	95581	1 gal. pail	250 ft ²	Clear	—	140	N/A	1-2	N/A
Big Foot™ Primer Sealer	94142	1 gal. kit	320 ft ²	Clear	500	140	120	3-6	6.5:1



Loctite Industrial

Henkel Loctite Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067
1-800-LOCTITE (562-8483)
www.loctite.com

Henkel Loctite Canada Inc.
2225 Meadowpine Blvd.
Mississauga, Ontario L5N 7P2
905-814-6511
800-263-5043 (within Canada)

Loctite, Natural Blue, and Big Foot are trademarks of Henkel Loctite Corporation, U.S.A.
© Copyright 2002. Henkel Loctite Corporation.
All rights reserved. 918/LT-3733 1/20